

Product Code: MD002SC

Luckinslive 389101659

Description: 10AX Ingot 2 Way Switch Module



General Information

Dimensions (mm)	25 (W) x 53 (H) x 20 (D)		
Finish	Satin Chrome		
Materials	Rocker Switch:	Urea	
	Switch Cover:	Stainless Steel	
	Terminal Screws:	Steel & Yellow Passivated	
	Internal Busbars:	Formed Pressed Brass	
Operating Voltage (AC)	250	Rear Housing: Nylon	
Inductive Load Rating (AX)	10	Terminals: Brass	
Load Rating Comments	Suitable for Fluorescent or Inductive Loads		
Termination Type	Screw		
Terminal Size (mm)	Ø3,5	Terminal Torque Value (Nm)	0.5
Terminal Capacity - Solid (mm ²)	4 x 1.5 or 2 x 2.5		
Modular Rocker Switches	Yes		
2 Way Switch	Yes		
Minimum Back Box Depth (mm)	16 (25 Flat Plate)		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

