Spec Sheet TSPOTLIP20











TSPOTLIP20


LED Emergency Twinspot Fitting

DESCRIPTION

Reduced battery capacity requirement allows a more compact design reducing the weight dramatically compared to traditional products facilitating easier installation, an ideal choice for internal applications requiring practical emergency lighting

FEATURES

- 3 hour non-maintained operation
- Individual indicator to show 'Lamps Healthy' and 'Charge'
- Horizontally and vertically adjustable heads, 180° rotation across the horizontal plane
- Battery Ni-Cd 3.6V 4.5Ah. Battery 1 year warranty -Replacement battery code: EB16



GENERAL INFORMATION			
Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface, Suspended
Product Warranty	5 Years	Battery Warranty	1 Year
Net Weight	1.4 kg		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Average Rated Life	50,000 h
Construction Materials Line 1	Polycarbonate	Dimensions - Height	310 mm
Dimensions - Width	280 mm	Dimensions - Depth	55 mm

PRODUCT INFORMATION			
Wattage Combined	3.4W	CCT Combined	6000K
Luminaire Lumens Combined	405 lm	lm/W Combined	119 lm/w
Beam Angle	120°	CRI	75
SDCM	<6	IP Rating	IP20
















P20

ACCESSORIES			
Product Code	Description	MOM / OPQ	
EB16	Ni-CAD 3.6V 4.5Ah Side by Side Battery	1/1	

PACKAGING		
Packaging Type	Plain Box	
Individual unit gross weight	1,284 g	
Pallet Layer Qty	48	
Pallet Layers	4	
Pallet Qty	192	
MOM / OPQ	1/6	







