



SBE7101



Gamma 1Row 7W 1RCD - 2x6A Ltg. RCBOs

Technical properties

Connection

| | |
|-----------------------------|---|
| Number of accessible phases | 1 |
|-----------------------------|---|

Installation, mounting

| | |
|----------------------------|------------------|
| Suitable for outdoor usage | No |
| Mounting on | Surface mounting |

Electric current

| | |
|---------------|------|
| Rated current | 63 A |
|---------------|------|

Equipment

| | |
|-----------------------------|-----|
| Number of rails | 1 |
| Number of rows | 1 |
| With lock | No |
| Has neutral terminal block | Yes |
| Has earthing terminal block | Yes |
| Has mounting plate | No |

Capacity

| | |
|-------------------|----|
| Number of modules | 13 |
|-------------------|----|

Functions

| | |
|----------------------------|----|
| Has protection main switch | No |
|----------------------------|----|

Scope of delivery

| | |
|-----------------------------|---|
| Number of RCCB in enclosure | 1 |
|-----------------------------|---|

Dimensions

| | |
|-----------------------|--------|
| Height | 250 mm |
| Width | 250 mm |
| Depth | 103 mm |
| Number of width units | 13 |

Cover, door

| | |
|---------------------------|-----|
| Number of locks | 0 |
| Door/cover is transparent | Yes |

Materials

| | |
|----------|------------------|
| Material | Polystyrene (PS) |
| RAL code | 9010 |
| Colour | Pure white |

| Safety | |
|-------------------------------|--------------------|
| Protection class | Isolation class II |
| Impact resistance IK | IK07 |
| Ingress Protection (IP) class | IP40 |
| Locking type | Snap on lock |