## **TRT031N**

# **Electronic Frost Thermostat** with Tamper Proof Cover

#### **Features & Benefits**

- Easily adjustable dial with clearly marked temperature scale
- Frost protection against the risk of freezing pipes
- 5°C to 10°C set temperature range
- Tamper proof cover protects thermostat settings
- Temperature swing adjustment (using DIP switches) between a 0.5 °C and 1°C
- PID control
- Switch Type: Single pole, single throw (SPST)
- · Surface mount with wall plate included



#### **Technical Data**

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Connection	3 Wire
Setting Type	Dial
Set Temperature Range	5°C to 10°C, User Adjustable
ErP Product Class	Class 1
Boiler Type	3CYC (Gas) or 6CYC (Oil) Dip Switch Adjustable
Temperature Swing (Hysteresis)	1°C or 0.5°C
PID Control	Supported (ON/OFF Switchable)

# Data sheet TRT031N

### Climate / Programastat Plus

Switch Type	Single Pole, Single Throw (SPST)
Mounting Hole Centres (mm)	60
Standby Consumption	<4W
Switch Rating	6A Resistive, 2A Inductive
Cable Entry(s)	Back Entry
Accessories (Included)	Rawl Plugs, Screws, Tamperproof Cover
Dimensions	Height 86mm, Width 88mm, Depth 38mm

### General

Weight (g)	160
Height (mm)	86
Width (mm)	88
Depth (mm)	38
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Rawl Plugs, Screws, Tamperproof Cover
EAN Number	5012483014370
Guarantee Period	3 Years
Trade Tariff Commodity Code	9032108090



### **Line Diagrams**



