

Product Code: MD075BK

Luckinslive 389103576

Description: 10A 3 Position Retractive Switch Module



General Information

| | | |
|--|---|--|
| Dimensions (mm) | 25 (W) x 57 (H) x 27 (D) | |
| Colour | Black | |
| Materials | Rocker Switch: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass | |
| Anti Microbial Certified | Yes | Rear Housing: Nylon |
| Operating Voltage (AC) | 250 | Terminal Screws: Steel & Yellow Passivated |
| Resistive Load Rating (A) | 10 | Internal Busbars: Formed Pressed Brass |
| Termination Type | Screw | |
| Terminal Size (mm) | Ø3.5 | Frequency (Hz) 50 |
| Terminal Capacity - Solid (mm ²) | 4 x 1.5 or 2 x 2.5 | Terminal Torque Value (Nm) 0.5 |
| Modular Rocker Switches | Yes | |
| 1 Pole 3 Position Switch | Yes | |
| Retractive Contact Options | Press to Make | |
| Minimum Back Box Depth (mm) | 25 (35 Flat Plate) | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 20 | |

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.