

# TRT032N

## Tamper Proof Room Thermostat

### Features & Benefits

- Easily adjustable dial with clearly marked temperature scale
- Tamper proof cover protects thermostat settings
- Frost Protection
- Temperature swing adjustment (using DIP switches) between a 0.5 °C and 1°C
- PID control
- Switch Type: Single pole, single throw (SPST)
- Surface mount with wall plate included



### Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Connection	3 Wire
Setting Type	Dial
Set Temperature Range	5°C to 30°C, User Adjustable
ErP Product Class	Class 1
Boiler Type	3CYC (Gas) or 6CYC (Oil) Dip Switch Adjustable
Temperature Swing (Hysteresis)	1°C or 0.5°C
PID Control	Supported (ON/OFF Switchable)
Switch Type	Single Pole, Single Throw (SPST)

# Data sheet

## TRT032N

Climate / Programastat Plus

Mounting Hole Centres (mm)	60
Standby Consumption	<4W
Switch Rating	6A Resistive, 2A Inductive
Cable Entry(s)	Back Entry
Accessories (Included)	Rawl Plugs, Screws, Tamperproof Cover
Dimensions	Height 86mm, Width 88mm, Depth 40mm

### General

Weight (g)	163
Height (mm)	86
Width (mm)	88
Depth (mm)	40
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Rawl Plugs, Screws, Tamperproof Cover
EAN Number	5012483014387
Guarantee Period	3 Years
Trade Tariff Commodity Code	9032108090

## Line Diagrams

