



VBE88101TSPD

Vega,2Row,5/8 WAY SPLIT LOAD CU,T/DOOR,2P ISOLATOR,SPD,1xRCD,2x6A LIGHTING RCBOs

Technical properties

| Instal | lation. | mounting |
|--------|---------|----------|
| | | |

| Mounting on | Surface mounting |
|---|------------------|
| Suitable for outdoor usage | No |
| Functions | |
| Has protection main switch | No |
| Overvoltage protection | Yes |
| Configuration | |
| Number of arc fault detection devices AFDD | 0 |
| Capacity | |
| Number of modules | 36 |
| Electric current | |
| Rated current | 80 A |
| Dimensions | |
| Depth | 145 mm |
| Height | 450 mm |
| Width | 370 mm |
| Number of width units | 18 |
| Thickness of sidewall | 2.50 mm |
| Cover, door | |
| Interlockable | Yes |
| Door/cover is transparent | Yes |
| Materials | |
| RAL code | 9010 |
| Colour | Pure white |
| Material | Polystyrene (PS) |
| Connection | |
| Number of accessible phases | 1 |
| Scope of delivery | |
| Number of earth leakage circuit breaker type A | 3 |
| Number of RCCB in enclosure | 1 |
| Number of RCCB in enclosure | |

| Equipment | |
|-------------------------------|--------------------|
| Number of light groups | 2 |
| Number of rows | 2 |
| With energy meter | No |
| Number of rails | 2 |
| With bell transformer | No |
| Safety | |
| Impact resistance IK | IK07 |
| Ingress Protection (IP) class | IP40 |
| Protection class | Isolation class II |